

Suitable applications

- ✓ Fitness/fun trails
- ✓ Cableways
- ✓ Multi-function play frames
- ✓ Springers
- ✓ Swings
- ✓ Pathways
- ✓ Gateways

SafaGrass™

More than one and a half million square metres of SafaGrass™ have been installed worldwide. Technix is one of the largest suppliers of playground safety surfacing in the UK.

The original safety grass mat

An environmentally friendly, non-slip, impact absorbing safety surface. The first choice and MOST competitively-priced safety surface available.



Benefits

- Absorbs shock and noise
- Moulded non-slip cellular structure with excellent durability, comfort and slip resistance
- Requires no special skills or tools, allowing quick and easy installation
- No base works required
- Ideal for green field sites, disappears from view once turf has grown
- Can be used on flat or sloping landscapes
- Suitable for all weather, extreme temperatures and resists wind uplift
- Wheelchair and pushchair accessible
- 10 year product guarantee
- Made from durable, safe recycled materials
- Can be installed all year round
- No ongoing maintenance required
- Up to 3m C.F.H.

technix

rubber and plastics ltd

Manufacturers, suppliers and installers of flooring and matting solutions

Call Now
0800 216 633

The Technical Bit...

Size: 1.5m x 1m x 23mm
Pallet Quantity: 60 tiles

Colour: Black
Weight: 14kg



BS EN 1177:2008

Critical Fall Height up to 3m (23mm)



BS EN 7188:1998

Slip Resistance



BS EN 4790:1987

Ease of Ignition



Environmentally Friendly

Manufactured from 80% recycled rubber



DDA Approved

Helps comply with the Disability Discrimination Act.



Drainage (SUDS compliant)

Free draining to provide a secure footing when wet.



European P.A.H. Passed
Brominated Flame Retardant test



TechMesh



We recommend TechMesh Lite be used as underlay when installing our grass mats.

Roll Size: 2m x 30m
Colour: Green or Black (colour may vary)
Mesh Size: 27mm x 24mm
Weight: 460g/m³

Simple to install

Please check the suitability of this product prior to installation as the C.F.H. figure will be affected by soil type, moisture and grass. Ensure you use 3 pegs along each perimeter length.

All our grass mats can be installed onto existing grass, seeded topsoil and new turf.

1. Mark out the area. Mats can be laid directly onto existing grassed areas. If the area is uneven, fill in with topsoil and ensure that it is compacted and seeded.
2. Leave about 150mm in from the outside edges.
3. Unroll the mesh and then lay the SafaGrass™ mats over the mesh area to be covered, cutting around any equipment or obstacles if necessary.
4. Cut about 75mm deep into the ground along the outside edge of the perimeter area to be covered using a grass edge cutter or similar.

5. Roll back the SafaGrass™ mat and, starting about 150mm in from the outside edge of the mats, use a spade angled towards the 75mm deep cut and cut the top turf away. This will leave a wedge shape channel. Continue around the perimeter of the mats. FIG. 1
6. Roll the SafaGrass™ mat back and down into the channel and, if the surface is hard, make a pilot hole prior to inserting the pegs. Peg the edge through the large holes in the mat and into the ground. Use 3 pegs per mat. You should now have a ramp edge all the way around.
7. Cover the ramped area with topsoil and seed. Bring the level back up to its original level and flatten into the existing ground. FIG. 2


Frequent watering is essential for optimum grass growth.

FIG. 1



Lift up soil/turf to knock pegs in

FIG. 2



Turf folded back down to hide pegs

Technix Rubber & Plastics Ltd
Unit 1&3, 362b Spring Road,
Sholing, Southampton
SO19 2PB, UK

t: +44 (0)23 8043 0040
f: +44 (0)23 8043 0043
e: sales@technix-rubber.com
w: www.technix-rubber.com



Certificate Number 5358



TOOLS:

5m tape measure, stanley knife, rubber gloves, hammer, grass edge cutter, spade, string or spray paint, rechargeable drill and 6mm drill bit.

Official Distributor/Installer

www.technix-rubber.com